





Selecting your fall protection PPE



Tractel® offers a full range of Personal Protective Equipment (PPE) in order to offer the support and safety necessary to protect yourself from the risk of falling when working at height. With over 70 years of industry experience, Tractel® has built a culture of safety through its ingenuity in manufacturing innovative and high quality products.

BASIC REQUIREMENTS OF PPE

- PPE must be suitable for the user.
- PPE must be properly maintained and stored.
- The user must be trained and / or informed in the use, care and maintenance of the equipment.
- Employers must evaluate the PPE requirements.
- Employees must report any loss or damage to the PPE.
- PPE must be compatible with the systems used.

CREATE YOUR FALL ARREST SYSTEM

To protect yourself in the event of a fall, you must have a fall arrest system that will stop and support you.

This fall arrest system must contain:

- An anchor
- Fall arrester (rope grab, self-retracting lanyard, energy absorber)
- A safety harness

Your fall arrest system can be supplemented with a lanyard that limits your movements within a secured area

While working at height using fall arrest equipment, a helmet must be worn that is certified to EN 397, with chin strap and 4 fixing points and classified as PPE category III.

Harness details

Attachment points

DORSAL

Fall arrest attachment point, marked with the letter "A", present on all EN 361-compliant harnesses.



STERNAL

EN 361-compliant fall arrest attachment point, marked with the letter "A", and "A/2".



THORACIC

EN 361-compliant fall arrest attachment point, marked with the letter "A", and EN 358-compliant work positioning point.



UMBILICAL

Attachment point for work while suspended (rope access work) EN 813. Cannot be used as an anchor point for fall arrest purposes.




LATERAL

Attachment point for EN 358-compliant work positioning systems. Cannot be used as an anchor point for fall arrest purposes.



Selecting the correct harness size



	S	M	XL	XXL*
A	60 - 100	80 - 120	100 - 160	130 - 170
B	75 - 100	90 - 110	100 - 150	130 - 170
C	45 - 60	45 - 70	45 - 80	80 - 90
D	55 - 65	65 - 80	80 - 90	90 - 100

in cm

*XXL sizes are only available for specific models, indicated directly on the pages concerned.